

Super charger for UPS battery bank

This special design super charger is used to charge the battery bank which used for UPS system to reduce the charging time.



MODEL		BATT-CHGR-96	BATT-CHGR-192
CAPACITY		750VA	1500VA
INPUT	Voltage	160 ~ 280VAC	
	Frequency	40Hz to 70Hz	
	Nominal input current	3.3A	6.6A
OUTPUT	Nominal output voltage	110VDC	219VDC
	Adjustable voltage range	60VDC to 120VDC	120VDC to 240VDC
	Rated Output current	7A	
	Battery type	AGM type	
	Efficiency	80%	
PROTECTION		Over Temperature protection	
ENVIRONMENTAL	Operation temperature	0°C to 40°C	
	Relative humidity	5 ~ 95% without condensation	
	Storage Temperature	-20°C to 80°C	
Mechanical	Dimension (DxWxH)mm	260x290x90	
	Weight	3.38kg	4.38kg

HELIOR
INSURE YOUR SYSTEM

HELIOR TECHNOLOGY CO., LTD.

3/F, Haibin Venture Park, Xingye Rd., Bao'An, Shenzhen, P.R.China

Post Code: 518102 Tel:(86 755) 8397 9799 /8397 8199 Fax:(86 755) 8397 8200

Mobile:(86) 136 030 90033 E-mail: edwin@heliortec.com Http:// www.heliortec.com